





ITEM	PART NO.	DESCRIPTION
1	R156-0438-004	Bolted Shipping Assembly, 1.563 OD X 4 FT, 4 SPF, 0°, 13 Shots
	R156-0438-007	Bolted Shipping Assembly, 1.563 OD X 7 FT, 4 SPF, 0°, 25 Shots
	R156-0438-011	Bolted Shipping Assembly, 1.563 OD X 11 FT, 4 SPF, 0°, 41 Shots
	R156-0438-015	Bolted Shipping Assembly, 1.563 OD X 15 FT, 4 SPF, 0°, 57 Shots
	R156-0438-021	Bolted Shipping Assembly, 1.563 OD X 21 FT, 4 SPF, 0°, 81 Shots
2	F107-0438-R04	Flat Strip, 1.070 OD X 4 FT, 4 SPF, 0°
	F107-0438-R07	Flat Strip, 1.070 OD X 7 FT, 4 SPF, 0°
	F107-0438-R11	Flat Strip, 1.070 OD X 11 FT, 4 SPF, 0°
	F107-0438-R15	Flat Strip, 1.070 OD X 15 FT, 4 SPF, 0°
	F107-0438-R21	Flat Strip, 1.070 OD X 21 FT, 4 SPF, 0°
3	B156-0400-004	Bolted Carrier, 1.563 OD X 4 FT, 4 SPF, 0°
	B156-0400-007	Bolted Carrier, 1.563 OD X 7 FT, 4 SPF, 0°
	B156-0400-011	Bolted Carrier, 1.563 OD X 11 FT, 4 SPF, 0°
	B156-0400-015	Bolted Carrier, 1.563 OD X 15 FT, 4 SPF, 0°
	B156-0400-021	Bolted Carrier, 1.563 OD X 21 FT, 4 SPF, 0°
C	RTG-1687-401NT	Charge, RTG 1-11/16" NT, HMX - uses Ribbon (Preferred) or 40 gr. Round Cord
	SDP-1687-401NTX	Charge, RTG 1-11/16" NTX, HMX - uses Ribbon (Preferred) or 40 gr. Round Cord
	SDP-1687-402NT3	Charge, RTG 1-11/16" NT3, HERO, SDP, HMX - uses Ribbon (Preferred) or 40 gr. Round Cord
	RTG-1687-301	Charge, RTG 1-11/16" DP, RDX - uses Ribbon (Preferred) or 40 gr. Round Cord
	RTG-1687-301BH	Charge, RTG 1-11/16" BH, RDX - uses Ribbon (Preferred) or 40 gr. Round Cord





SPECIFICATIONS		
Pressure Rating	155.1 Mpa	22,500 psi
Temperature	UP TO 288°C	UP TO 550°F
Max O.D. before Firing	39.67 mm	1.562"
Max O.D. after Firing (in fluid)	41.4 mm	1.63"
Max O.D. after Firing (in gas)	42.85 mm	1.687"
Gun Weight Loaded	4.1 kg/m	2.75 lb/ft

ITEM	PART NO.	DESCRIPTION
4	RTG-1687-112	Shooting Adapter, 1-11/16" O.D.
5	RTG-1687-108	Tandem Sub, 1-11/16" Without Dart Seal
	RTG-1687-109	Tandem Sub, 1-11/16" With Dart Seal
6	RTG-1687-115	Bull Plug, 1-11/16"
7	RTG-1687-116	Blast Sleeve, 1-11/16"
8	PUR-0500-032	Socket Hd. Cap Screw, 1/4-20 x 1/4"
	PUR-0500-033	Socket Hd. Cap Screw, 1/4-20 x 3/8"
9	OOO-N569-214	O-Ring #214 Nitrile
	OOO-V569-214	O-Ring #214 Viton
A	A538010	Det Cord - Ribbon, 40 gr. RDX, Nylon LS
	A545010	Det Cord - Ribbon, 40 gr. HMX, Nylon LS
	A539010	Det Cord - Round, 40 gr. RDX, Nylon LS
	A544010	Det Cord - Round, 40 gr. HMX, Nylon LS

