



Item	Part No.	Description
A	26-101-5715-10	Slick Gun System, 101mm x 1.0m, 13 spm, 30° Spiral
	26-101-2115-10	Slick Gun System, 101mm x 1.0m, 13 spm, 60° Spiral
	26-101-0415-10	Slick Gun System, 101mm x 1.0m, 13 spm, 90° Spiral
	26-101-XX15-20	Slick Gun System, 101mm x 2.0m, 13 spm, 30°, 60°, 90° Spiral
	26-101-XX15-30	Slick Gun System, 101mm x 3.0m, 13 spm, 30°, 60°, 90° Spiral
	26-101-XX15-40	Slick Gun System, 101mm x 4.0m, 13 spm, 30°, 60°, 90° Spiral
	26-101-XX15-50	Slick Gun System, 101mm x 5.0m, 13 spm, 30°, 60°, 90° Spiral
	26-101-XX15-60	Slick Gun System, 101mm x 6.0m, 13 spm, 30°, 60°, 90° Spiral
1	27-051-5715-10	Tube Strip, 51mm x 1.0m, 13 spm, 30° Spiral
	27-051-2115-10	Tube Strip, 51mm x 1.0m, 13 spm, 60° Spiral
	27-051-0415-10	Tube Strip, 51mm x 1.0m, 13 spm, 90° Spiral
	27-051-XX15-20	Tube Strip, 51mm x 2.0m, 13 spm, 30°,60°,90° Spiral
	27-051-XX15-30	Tube Strip, 51mm x 3.0m, 13 spm, 30°,60°,90° Spiral
	27-051-XX15-40	Tube Strip, 51mm x 4.0m, 13 spm, 30°,60°,90° Spiral
	27-051-XX15-50	Tube Strip, 51mm x 5.0m, 13 spm, 30°,60°,90° Spiral
	27-051-XX15-60	Tube Strip, 51mm x 6.0m, 13 spm, 30°,60°,90° Spiral
2	26-101-0000-10	Carrier, 101mm x 1.0m
	26-101-0000-20	Carrier, 101mm x 2.0m
	26-101-0000-30	Carrier, 101mm x 3.0m
	26-101-0000-40	Carrier, 101mm x 4.0m
	26-101-0000-50	Carrier, 101mm x 5.0m
	26-101-0000-60	Carrier, 101mm x 6.0m
3	30-101-0001-00	101mm Top Sub, Wireline Systems
	30-101-0001-75	101mm Top Sub, TCP
4	30-101-0003-00	101mm Bottom Sub
5	OOO-N569-230	O-Ring, #230, Quick Change, 90 Duro Nitrile
6	OOO-N569-236	O-Ring, #236, 101mm Carrier, 90 Duro Nitrile
7	DET-0010-001	Detonating Cord End Cover
B	A578010	Detonating Cord -LS 80gr., RDX
	A571010	Detonating Cord -LS 80gr., HMX
C	SLK-4000-324SG	Charge, 16g RDX, DP, Shallow Gas
D	-	Resistorized Detonator - (Ref. Detonator Section)

Note: Replace "XX" with 57 for 30° phasing, 21 for 60° phasing and 04 for 90° phasing.

Specifications		
Pressure Rating	41.4 Mpa	6000 psi
Temperature	Up To 107 °C	Up To 300 °F
Tensile Strength	57,400 daN	129,000 lbf

