



**American  
Petroleum  
Institute**

*address  
off*

**REGISTERED DATA SHEET PERFORATING SYSTEM EVALUATION, API RP 19B SECTION 1**

Service Company AVAILABLE TO ALL FROM OWEN OIL TOOLS Explosive Weight 25.0 gm, RDX powder, Case Material STEEL  
 Gun OD & Trade Name 3 3/8" TAG - 6SPF, 60 DEGREE, GH Max. Temp, °F 325 1 hr 3 hr 24 hr 100 hr 200 hr  
 Charge Name 3 3/8" TAG, DP, RDX, GOOD HOLE Maximum Pressure Rating 22,000 psi, Carrier Material STEEL  
 Manufacturer Charge Part No. TAG-3375-302 Date of Manufacture 22-FEB-2003 Shot Density Tested 6 Shots/ft  
 Gun Type SCALLOPED, RETRIEVABLE EXPENDABLE HOLLOW CARRIER Recommended Minimum ID for Running 3.75 in.  
 Phasing Tested 60 degrees, Firing Order X Top Down, X Bottom Up Available Firing Mode X Selective, X Simultaneous  
 Debris Description N/A Debris Weight N/A gm/charge, Debris N/A in<sup>3</sup>/charge  
 Remarks \_\_\_\_\_

**SECTION 1 - CONCRETE TARGET**

Casing Data 4.5" OD, Weight 11.6 lb/ft, L-80 API Grade, Date of Section 1 Test 24-MAR-2003  
 Target Data 60" OD, Amount of Cement 9105 lb., Amount of Sand 18210 lb., Amount of Water 4740 lb.  
 Date of Compressive Strength Test 2-APR-2003, Briquette Compressive Strength 7925 psi, Age of Target 32 days

Shot No.	No. 1	No. 2	No. 3	No. 4	No. 5	No. 6	No. 7	No. 8	No. 9	No. 10	No. 11	
Clearance, in.....	0.14	0.45	0.63	0.45	0.14	0.00	0.14	0.45	0.63	0.45	0.14	
Casing Hole Diameter, Short Axis, in.....	0.55	0.57	0.52	0.55	0.55	0.55	0.55	0.55	0.51	0.56	0.53	
Casing Hole Diameter, Long Axis, in.....	0.56	0.58	0.57	0.56	0.55	0.57	0.58	0.57	0.52	0.59	0.56	
Average Casing Hole Diameter, in.....	0.56	0.58	0.55	0.56	0.55	0.56	0.57	0.56	0.52	0.58	0.55	
Total Depth, in.....	19.25	18.00	20.75	18.25	16.75	16.88	16.25	18.88	19.75	18.00	17.75	
Burr Height, in.....	0.07	0.06	0.07	0.04	0.10	0.08	0.03	0.07	0.10	0.09	0.11	
Shot No.	No. 12	No. 13	No. 14	No. 15	No. 16	No. 17	No. 18	No. 19	No. 20	No. 21	No. 22	Average
Clearance, in.....	0.00	0.14	0.45	0.63	0.45	0.14	0.00					xxx
Casing Hole Diameter, Short Axis, in.....	0.55	0.56	0.55	0.51	0.54	0.53	0.55					0.54
Casing Hole Diameter, Long Axis, in.....	0.58	0.57	0.56	0.54	0.54	0.55	0.56					0.56
Average Casing Hole Diameter, in.....	0.57	0.57	0.55	0.53	0.54	0.54	0.56					0.55
Total Depth, in.....	16.75	18.75	20.63	16.00	19.25	18.75	16.25					18.16
Burr Height, in.....	0.09	0.05	0.07	0.10	0.11	0.08	0.10					0.08

**WITNESSING INFORMATION**

Date of Notice of Intent to Test: February 28, 2003 Witnessed by: Truda Stevens  
 Other Activities Witnessed: Target Pouring      Briquette: Preparation      Testing      Burr Height Measurements      Samples Taken: Concrete X Casing X

**CERTIFICATION**

I certify that these tests were made according to the procedures as outlined in API RP 19B: Recommended Practices for Evaluation of Well Perforators, First Edition, November 2000. All of the equipment used in these tests, such as the guns, jet charges detonator cord, etc., was standard equipment with our company for the use in the gun being tested and was not changed in any manner for the test. Furthermore, the equipment was chosen at random from stock and therefore will be substantially the same as the equipment, which would be furnished to perforate a well for any operator. The American Petroleum Institute neither endorses these test results nor recommends the use of the perforator system described.

X CERTIFIED BY *David Chat* VICE PRESIDENT - ENGINEERING 9-23-03 OWEN OIL TOOLS 12001 County Road 1000 Godley, TX, USA 76044  
 RECERTIFIED (Company Official) (Title) (Date) (Company) (Address)