



ITEM	PART NO.	DESCRIPTION	
1	TAG-4000-280	Top Sub 4" Adapts to TCP or Wireline Systems	
	SLK-4000-001	Carrier 4"X2' 4 Shot Slick Gun	
	SLK-4000-002	Carrier 4"X3' 8 Shot Slick Gun	
	SLK-4000-003	Carrier 4"X4' Threaded Slick Gun	
	SLK-4000-004	Carrier 4"X7' Threaded Slick Gun	
	SLK-4000-009	Carrier 4"X9' Threaded Slick Gun	
	2	SLK-4000-005S	Carrier 4"X10.66' Threaded Slick Gun
	SLK-4000-005	Carrier 4"X11' Threaded Slick Gun	
	SLK-4000-013	Carrier 4"X13' Threaded Slick Gun	
	SLK-4000-006	Carrier 4"X15' Threaded Slick Gun	
	SLK-4000-016	Carrier 4"X16' Threaded Slick Gun	
	SLK-4000-007	Carrier 4"X21' Threaded Slick Gun	
	3	SLK-3125-222	Twisted Strip, 90° 4spf 40 shot (10' long)
	SLK-3125-223	Twisted Strip, 60° 4spf 40 shot (10' long)	
4	TAG-4000-078	Bull Plug 4"	
5	OOO-N569-230	O-Ring, #230, 90 Duro Nitrile - (Quick Change)	
6	OOO-N569-236	O-Ring, #236, 90 Duro Nitrile - (4" Carrier)	
7	DET-0010-001	Detonating Cord End Cover	
8	OOO-R569-128	Charge Retaining O-Ring	
A	A580010	Detonating Cord, 80 gr., RDX - see ref. section	
C	SDP-3125-311NT4	Charge, RDX, SDP - NT4 - SUPER HERO	
	SDP-3375-311NT	Charge, RDX, SDP	
	TAG-3375-311	Charge, RDX, DP/GH	
	TAG-3375-311L	Charge, RDX, DP	
	TAG-3375-311SL	Charge, RDX, DP	
	HSC-3375-301	Charge, RDX, BH	
D	--	Detonator (See Detonator Reference Section)	

SPECIFICATIONS		
Pressure Rating	41.4 Mpa	6,000 psi
Temperature	UP TO 107° C	UP TO 300° F
Tensile Strength	40,824 kg	90,000 lbs
Maximum Length	12 m	40 ft
Maximum O.D. after Firing	11.4	4-1/2"

Note: Shoot in Fluid Only

Strips can be cut to length as required

Available, SLK-3125-088 - Locking Strip Collar with PUR-0502-045 - Adjusting Bolt (1/4"-20X1" Hex Head Bolt)