



Technical Bulletin
Engineering Department
Owen Oil Tools Division

Subject: **TAG-3375-331, New Charge Release**

From: **Matthew Clay**

Date: **11-16-2011**

Distribution: **West, Jeff; Weisner, Les; Schaffer, Brett; Owen Buyer Planners; Owen Engineering; Owen Receiving; Owen International All; Owen Sales & Marketing; Owen Quality Control; Owen Machine Shop; Owen Ballistics Manufacturing; Owen Warehouses All; Lisle, Josh; Campbell, Steve**

Reference: **PRJ-0864**

Document Number: **PRJ-0864-TB-00 (Rev 00)**

Owen Oil Tools is happy to announce the release of the new TAG-3375-331 DP/GH. This charge can be used in existing gun systems that use the -08 charge code. The latest revision to Engineered Perforator Analysis (EPA) has been updated to include this new data.

The TAG-3375-331 was requested for applications that require a larger hole size than a typical 25 gram DP charge, while also maintaining high performance requirements for penetration. In RP-43, the charge averaged 0.56" and 31.14" of penetration in 4-1/2" 11.6# L-80 casing. Attached to this technical bulletin is the datasheet.

If you have any questions about this charge please feel free to contact your local Owen representative or Owen Engineering.



TAG-3375-331 RP43
Data

Matthew Clay

Engineering Manager, Energetics Technology Group
Owen Oil Tools LP | www.corelab.com/owen | (214) 662-1036

CERTIFICATION DATA SHEET

3-3/8" OD, TAG, 6 SPF, 60°, 25G, RAPTOR (TAG-3375-331)

FORM 43F

PERFORATING SYSTEM EVALUATION, RP 43, SECTIONS 1 AND 2

TAG-3375-331

Service Company <u>AVAILABLE TO ALL FROM OWEN OIL TOOLS, INC.</u>	Explosive Weight <u>25</u> gm, <u>RDX</u> powder, Case Material <u>STEEL</u>
Gun OD & Trade Name <u>3-3/8" OD, TAG, 6 SPF, 60°, 25G, RAPTOR (TAG-3375-331)</u>	Max. Temp, F <u>330</u> 1 hr <u> </u> 3 hr <u> </u> 24 hr <u> </u> 100 hr <u> </u> hr
Charge Name <u>PERFORATOR, 3-3/8", SDP, 25G, RAPTOR, RDX</u>	Maximum Pressure Rating <u>20,000</u> psi, Carrier Material <u>STEEL</u>
Manufacturer Charge Part No. <u>TAG-3375-331</u> Date of Manufacture <u>26-Sep-11</u>	Shot Density <u>6</u> shots/ft
Gun Type <u>SCALLPOED, EXPE</u>	Recommended Minimum ID for Running <u>3.800</u> in.
Phasing Tested <u>60</u> degrees, Firing Order <u>X</u> Top down, <u> </u> Bottom up	Available Firing Mode <u>X</u> Selective, <u>X</u> Simultaneous.
Debris Description <u>SMALL STEEL PIECES</u>	Debris Weight <u>N/A</u> gm/charge, Debris <u>N/A</u> in.³/charge
Remarks <u>HMX VERSION AVAILABLE AS TAG-3375-431</u>	

SECTION 1 - CONCRETE TARGET

Casing Data <u>4 1/2</u>	OD, Weight <u>11.6</u> lb/ft,	L-80	API Grade, Date of Concrete Test	<u>24-Oct-11</u>			
Target Data <u>84"</u>	OD, Briquet Compressive Strength	<u>6213</u>	psi, Age of Target	<u>29</u> days			

Shot No.	No. 1	No. 2	No. 3	No. 4	No. 5	No. 6	No. 7	No. 8	No. 9	No. 10
Clearance, in.	<u>0.00</u>	<u>0.14</u>	<u>0.45</u>	<u>0.83</u>	<u>0.45</u>	<u>0.14</u>	<u>0.00</u>	<u>0.14</u>	<u>0.45</u>	<u>0.83</u>
Casing Hole Diameter, Short Axis, in.	<u>0.53</u>	<u>0.56</u>	<u>0.57</u>	<u>0.58</u>	<u>0.55</u>	<u>0.54</u>	<u>0.55</u>	<u>0.54</u>	<u>0.54</u>	<u>0.59</u>
Casing Hole Diameter, Long Axis, in.	<u>0.54</u>	<u>0.56</u>	<u>0.57</u>	<u>0.59</u>	<u>0.57</u>	<u>0.55</u>	<u>0.55</u>	<u>0.54</u>	<u>0.57</u>	<u>0.59</u>
Average Casing Hole Diameter, in.	<u>0.54</u>	<u>0.56</u>	<u>0.57</u>	<u>0.59</u>	<u>0.56</u>	<u>0.55</u>	<u>0.55</u>	<u>0.54</u>	<u>0.56</u>	<u>0.59</u>
Total Depth, in.	<u>27.40</u>	<u>32.80</u>	<u>31.90</u>	<u>30.20</u>	<u>32.20</u>	<u>32.60</u>	<u>27.80</u>	<u>33.10</u>	<u>31.70</u>	<u>29.80</u>
Burr Height, in.	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>

Shot No.	No. 11	No. 12	No. 13	No. 14	No. 15	No. 16	No. 17	No. 18	No. 19	No. 20	Average
Clearance, in.	<u>0.45</u>	<u>0.14</u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>
Casing Hole Diameter, Short Axis, in.	<u>0.56</u>	<u>0.56</u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u>0.56</u>
Casing Hole Diameter, Long Axis, in.	<u>0.58</u>	<u>0.56</u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u>0.56</u>
Average Casing Hole Diameter, in.	<u>0.57</u>	<u>0.56</u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u>0.56</u>
Total Depth, in.	<u>31.40</u>	<u>32.80</u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u>31.14</u>
Burr Height, in.	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u>0.00</u>

Remarks PENETRATION NORMALIZED TO 5000 PSI CONCRETE WOULD BE 33.03" (5% PER 1000 PSI)

SECTION 2 - BEREA SANDSTONE CORE TARGET

	Shot No.	No. 1	No. 2	No. 3	No. 4	No. 5	No. 6	Average
Berea Bulk Porosity, <u> </u>	Faceplate Hole Diameter, Short Axis, in.	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>
	Faceplate Hole Diameter, Long Axis, in.	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>
Date of Berea Test <u> </u>	Average Faceplate Hole Diameter, in.	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>
	Total Depth, in.	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>

CERTIFICATION

Type of Certification: Self Third Party

I certify that these tests were made according to the procedures as outlined in RP 43: Recommended Practices for Evaluation of Well Perforators, Fifth Edition, January 1991. All of the equipment used in these tests, such as the guns, jet charges, detonator cord, etc., was standard with our company for use in the gun being tested, and was not changed in any manner for the test. Furthermore, the equipment was chosen at random from stock and therefore will be substantially the same as the equipment which would be furnished to perforate a well for any operator.

CERTIFIED BY	<u>Matthew Clay</u>	Ballistics Engineering Manager	31-Oct-11	OWEN OIL TOOLS, INC	12001 CR 1000, GODLEY, TX, 76028
RECERTIFIED	(Company Officer)	(Title)	(Date)	(Company)	(Address)