

**REGISTERED DATA SHEET PERFORATING SYSTEM EVALUATION, API RP 19B SECTION 1**

Service Company AVAILABLE TO ALL FROM OWEN OIL TOOLS Explosive Weight 20.0 gm, HMX powder, Case Material ZINC  
 Gun OD & Trade Name 3 3/8" TAG, 6SPF, 60 deg, BH Max. Temp, °F 400 1 hr 3 hr 24 hr 100 hr 200 hr  
 Charge Name PERF. 3-3/8" TAG, HMX, 20g, BH Maximum Pressure Rating 25,000 psi, Carrier Material OWEN SPEC. STEEL  
 Manufacturer Charge Part No. HSC-3375-401F Date of Manufacture: 15-DEC-2004 Shot Density Tested 6 Shots/ft  
 Gun Type SCALLOPED, RETRIEVABLE EXPENDABLE HOLLOW CARRIER Recommended Minimum ID for Running 3.80 in.  
 Phasing Tested 60 degrees, Firing Order X Top Down, Bottom Bottom Up Available Firing Mode X Selective, X Simultaneous  
 Debris Description N/A Debris Weight N/A gm/charge, Debris N/A in<sup>3</sup>/charge  
 Remarks \_\_\_\_\_

**SECTION 1 - CONCRETE TARGET**

Casing Data 5.50" OD, Weight 17 lb/ft, L-80 API Grade, Date of Section 1 Test 15-JAN-2005  
 Target Data 36" OD, Amount of Cement 8984 lb., Amount of Sand 18075 lb., Amount of Water 4707 lb.  
 Date of Compressive Strength Test 14-JAN-2005, Briquette Compressive Strength 7605 psi, Age of Target 30 days

Shot No.	No. 1	No. 2	No. 3	No. 4	No. 5	No. 6	No. 7	No. 8	No. 9	No. 10	No. 11	
Clearance, in.....	0.29	1.05	1.52	1.05	0.29	0.00	0.29	1.05	1.52	1.05	0.29	
Casing Hole Diameter, Short Axis, in.....	0.61	0.58	0.49	0.60	0.61	0.60	0.60	0.56	0.49	0.61	0.60	
Casing Hole Diameter, Long Axis, in.....	0.64	0.60	0.51	0.61	0.62	0.61	0.63	0.59	0.54	0.62	0.61	
Average Casing Hole Diameter, in.....	0.63	0.59	0.50	0.61	0.62	0.61	0.62	0.58	0.52	0.62	0.61	
Total Depth, in.....	6.30	6.80	6.80	6.80	7.05	7.05	6.80	7.05	6.30	7.05	6.80	
Burr Height, in.....	0.09	0.04	0.01	0.03	0.08	0.07	0.09	0.04	0.02	0.03	0.10	
Shot No.	No. 12	No. 13	No. 14	No. 15	No. 16	No. 17	No. 18	No. 19	No. 20	No. 21	No. 22	Average
Clearance, in.....	0.00	0.29	1.05	1.52	1.05	0.29	0.00					xxx
Casing Hole Diameter, Short Axis, in.....	0.59	0.62	0.56	0.52	0.59	0.63	0.61					0.58
Casing Hole Diameter, Long Axis, in.....	0.63	0.63	0.59	0.54	0.61	0.64	0.63					0.60
Average Casing Hole Diameter, in.....	0.61	0.63	0.58	0.53	0.60	0.64	0.62					0.59
Total Depth, in.....	7.30	6.30	6.80	7.30	6.80	7.30	6.30					6.83
Burr Height, in.....	0.07	0.06	0.06	0.04	0.03	0.11	0.08					0.06

**WITNESSING INFORMATION**

Date of Notice of Intent to Test: January 3, 2005 Witnessed by: Ray Feigenbutz  
 Other Activities Witnessed: Target Pouring      Briquette: Preparation      Testing      Burr Height Measurements X Samples Taken: Concrete X Casing X

**CERTIFICATION**

I certify that these tests were made according to the procedures as outlined in API RP 19B: Recommended Practices for Evaluation of Well Perforators, First Edition, November 2000. All of the equipment used in these tests, such as the guns, jet charges detonator cord, etc., was standard equipment with our company for the use in the gun being tested and was not changed in any manner for the test. Furthermore, the equipment was chosen at random from stock and therefore will be substantially the same as the equipment, which would be furnished to perforate a well for any operator. The American Petroleum Institute neither endorses these test results nor recommends the use of the perforator system described.

X CERTIFIED BY [Signature] Ballistics Engineering Manager 1-15-2005 OWEN OIL TOOLS 12001 County Road 1000 Godley, TX, USA 76044  
 RECERTIFIED \_\_\_\_\_ (Company Official) (Title) (Date) (Company) (Address)