



REGISTERED DATA SHEET PERFORATING SYSTEM EVALUATION, API RP 19B SECTION 1

Service Company AVAILABLE TO ALL FROM OWEN OIL TOOLS Explosive Weight 13.9 gm, HMX powder, Case Material STEEL
 Gun OD & Trade Name 2 1/8" SPIRAL SHOGUN RAPTOR Max. Temp, °F 400 1 hr 3 hr 24 hr 100 hr 200 hr
 Charge Name 2 1/8" SHOGUN RAPTOR HMX Maximum Pressure Rating 20,000 psi, Carrier Material STEEL
 Manufacturer Charge Part No. STP-2125-401NTX Date of Manufacture 15-SEP-2003 Shot Density Tested 6 Shots/ft
 Gun Type WIRELINE THROUGH TUBING STRIP, SEMI-EXPENDABLE Recommended Minimum ID for Running 2.18 in.
 Phasing Tested 40 degrees, Firing Order X Top Down, Bottom Up Available Firing Mode Selective, X Simultaneous
 Debris Description N/A Debris Weight N/A gm/charge, Debris N/A in³/charge
 Remarks THE 2 1/8" SHOGUN SYSTEM INCLUDES 4 OR 6 SPF, 0 PHASE STRIP, +/- 45 DEGREE STRIP, PHASEABLE LINK, AND SPIRAL PHASED (60° & 40°) RETRIEVABLE STRIP.

SECTION 1 - CONCRETE TARGET

Casing Data 5.5 OD, Weight 17.0 lb/ft, L-80 API Grade, Date of Section 1 Test 20-OCT-2003
 Target Data 72 OD, Amount of Cement 7415 lb., Amount of Sand 14950 lb., Amount of Water 3876 lb.
 Date of Compressive Strength Test 21-OCT-2003, Briquette Compressive Strength 6781 psi, Age of Target 33 days

Shot No.	No. 1	No. 2	No. 3	No. 4	No. 5	No. 6	No. 7	No. 8	No. 9	No. 10	No. 11
Clearance, in.....	1.73	0.73	0.16	0.00	0.16	0.73	1.76	2.64	2.64	1.76	0.73
Casing Hole Diameter, Short Axis, in.....	0.24	0.27	0.27	0.25	0.26	0.28	0.26	0.24	0.26	0.26	0.26
Casing Hole Diameter, Long Axis, in.....	0.25	0.34	0.27	0.26	0.27	0.31	0.28	0.27	0.31	0.33	0.37
Average Casing Hole Diameter, in.....	0.25	0.31	0.27	0.26	0.27	0.30	0.27	0.26	0.29	0.30	0.32
Total Depth, in.....	24.55	24.05	26.55	25.30	28.05	LOST	26.55	24.30	23.30	26.30	29.18
Burr Height, in.....	0.05	0.07	0.05	0.01	0.03	0.07	0.06	0.04	0.08	0.07	0.08

Shot No.	No. 12	No. 13	No. 14	No. 15	No. 16	No. 17	No. 18	No. 19	No. 20	No. 21	No. 22	Average
Clearance, in.....	0.16	0.00	0.16	0.73	1.76	2.64	2.64	1.76	0.73	0.16	0.00	xxx
Casing Hole Diameter, Short Axis, in.....	0.27	0.26	0.27	0.27	0.31	0.24	0.24	0.31	0.29	0.26	0.23	0.27
Casing Hole Diameter, Long Axis, in.....	0.30	0.31	0.31	0.35	0.32	0.27	0.27	0.34	0.33	0.29	0.26	0.31
Average Casing Hole Diameter, in.....	0.29	0.29	0.29	0.31	0.32	0.26	0.26	0.33	0.31	0.28	0.25	0.28
Total Depth, in.....	24.05	26.30	27.30	24.30	LOST	23.30	22.55	22.80	28.30	23.30	24.55	25.25
Burr Height, in.....	0.07	0.01	0.06	0.10	0.06	0.05	0.05	0.07	0.09	0.04	0.01	.06

WITNESSING INFORMATION

Date of Notice of Intent to Test: September 29, 2003 Witnessed by: Ed Langford
 Other Activities Witnessed: Target Pouring Briquette: Preparation Testing Burr Height Measurements X Samples Taken: Concrete X Casing X

CERTIFICATION

I certify that these tests were made according to the procedures as outlined in API RP 19B: Recommended Practices for Evaluation of Well Perforators, First Edition, November 2000. All of the equipment used in these tests, such as the guns, jet charges detonator cord, etc., was standard equipment with our company for the use in the gun being tested and was not changed in any manner for the test. Furthermore, the equipment was chosen at random from stock and therefore will be substantially the same as the equipment, which would be furnished to perforate a well for any operator. The American Petroleum Institute neither endorses these test results nor recommends the use of the perforator system described.

X CERTIFIED BY *David Pratt* VICE PRESIDENT - ENGINEERING 10-22-03 OWEN OIL TOOLS 12001 County Road 1000 Godley, TX, USA 76044
 _____ RECERTIFIED _____ (Company Official) (Title) (Date) (Company) (Address)