



Designed to perform in post-stimulation environments, Completion Profiler is the most accurate and versatile production profile logging tool in the industry. Run in conjunction with the SPECTRASCAN imager, Completion Profiler provides a robust evaluation of completion effectiveness and post-fracture production performance in a single trip deployment.

ADVANCED FEATURES

- Spinner is a proprietary design for high sand environments
- Fluid ID/ single phase, 2-phase and 3-phase analysis
- PLATO analytical software/ global stochastic statistical analysis

CONNECTION

Standard 5/8" sucker rod

TOOL COMPONENTS

- Spinner/ Single In-Line
- 3 Centralizers
- Fluid ID/ Gamma Density, Electrical Capacitance
- Pressure and Temperature Sensors
- Casing Collar Locator/ Induction
- SPECTRASCAN Detector/ Spectral Gamma Ray
- Batteries/ High Temperature Lithium

DEPLOYMENT METHODS

- Washpipe
- Slickline
- Electric Line
- Tubing/ Coiled Tubing

TOOL SPECIFICATIONS

Temperature:	up to 300F/ 150C	up to 350F/ 176C
Pressure:	20,000psi	20,000psi
Outside Diameter:	1.69in/ 43mm	1.75in/ 44.45mm
Length:	26.65ft/ 8.12m	26.65ft/ 8.12m